

# AsteRx SB3 Pro+

Advanced housed GNSS positioning and heading receiver



**AsteRx SB3 Pro+ is the most flexible housed multi-frequency GNSS receiver. It can be used as a rover or a base station with ultra-high update rate and logging functionality. Housed in a ruggedized enclosure it delivers top performance even in the harshest environments.**

## KEY FEATURES

- ▶ **All in view, multi-constellation, multi-frequency satellite tracking**
- ▶ **Sub-degree GNSS heading & pitch or heading & roll**
- ▶ **AIM+ Interference monitoring and mitigation function**
- ▶ **Flexibility to be used either as a rover or a base station**
- ▶ **GNSS+ algorithms guaranteeing reliable performance**
- ▶ **Compact, yet rugged design**

## Reliable heading performance

With dual-antenna input, AsteRx SB3 Pro+ provides precise, reliable and positioning independent heading combined with centimeter-level RTK. GNSS heading provides unmatched performance in both static and dynamic conditions removing the reliance on vehicle dynamics or magnetic sensors.

## Feature-rich in a compact design

Simultaneous multi-constellation, multi-frequency tracking combined with the GNSS+ toolset and high-update rate, low-latency output mean that AsteRx SB3 Pro+ is ideally suited for any space-constrained industrial application under any conditions.

## Ease of integration

The AsteRx SB3 Pro+ integrates seamlessly into any system thanks to fully documented interfaces, commands and data messages. Septentrio's open interfaces and software tools (WebUI, RxTools) make it easy to integrate, configure and control the AsteRx SB3 Pro+.

# AsteRx SB3 Pro+

## FEATURES

### GNSS signals

544 Hardware channels for simultaneous tracking of most visible signals:

- ▶ GPS: L1 C/A, L2C, L2 P(Y), L5
- ▶ GLONASS: L1 C/A, L2C/A, L3, L2P
- ▶ BeiDou: B1I, B1C, B2a, B2I, B3I
- ▶ Galileo: E1, E5a, E5b
- ▶ QZSS: L1 C/A, L2C, L5
- ▶ NavIC: L5
- ▶ SBAS: EGNOS, WAAS, GAGAN, MSAS, SDCM

### Septentrio's patented GNSS+ technologies

- ▶ **AIM+** unique anti-jamming and monitoring system against narrow and wideband interference
- ▶ **APME+** a posteriori multipath estimator for code and phase multipath mitigation
- ▶ **LOCK+** superior tracking robustness under heavy mechanical shocks or vibrations
- ▶ **IONO+** advanced scintillation mitigation
- ▶ **RAIM+** (Receiver Autonomous Integrity Monitoring)

### Formats

Septentrio Binary Format (SBF), fully documented with sample parsing tools  
NMEA 0183, v3.01, v4.0  
RTCM v2.x, v3.x (MSM messages included)  
CMR v2.0 and CMR+ (CMR+ input only)

### Connectivity

3 Hi-speed serial ports (RS232)  
Ethernet port (TCP/IP, UDP, LAN 10/100 Mbps)  
Power over ethernet  
1 High-speed/full-speed USB device port  
2 Event markers  
FTP server  
16 GB internal memory

## SUPPORTING COMPONENTS

Embedded Web UI with full control and monitoring functionality.

RxTools, a complete and intuitive GUI tool set for receiver control, monitoring, data analysis and conversion.

GNSS receiver communication SDK. Available for both Windows and Linux.

### Optional accessories

- ▶ Antennas
- ▶ GeoTagZ re-processing software and SDK library for UAS applications

## PERFORMANCE

### RTK performance<sup>1,2,3</sup>

Horizontal accuracy	0.6 cm + 0.5 ppm	
Vertical accuracy	1 cm + 1 ppm	
Initialisation	7 s	

### GNSS attitude accuracy<sup>1,2</sup>

Antenna separation	Heading	Pitch/Roll
1 m	0.15°	0.25°
5 m	0.03°	0.05°

### Position accuracy<sup>1,2</sup>

	Horizontal	Vertical
Standalone	1.2 m	1.9 m
SBAS	0.6 m	0.8 m
DGNSS	0.4 m	0.7 m

### Velocity accuracy<sup>1,2</sup>

0.03 m/s

### Maximum update rate

Position	100 Hz
Measurements	100 Hz

### Latency<sup>4</sup>

<10 ms

### Time precision

xPPS out <sup>5</sup>	5 ns
Event accuracy	< 20 ns

### Time to first fix

Cold start <sup>6</sup>	< 45 s
Warm start <sup>7</sup>	< 20 s
Re-acquisition	avg. 1 s

### Tracking performance (C/N0 threshold)

Tracking	20 dB-Hz
Acquisition	33 dB-Hz

## PHYSICAL AND ENVIRONMENTAL

### SWaP

Size	102 x 36 x 118 mm / 4.0 x 1.4 x 4.6 in
Weight	497 g / 1.1 lb
Input voltage	5 to 36 VDC

### Power consumption

GPS/GLO L1/L2	1.1 W
All signals, all GNSS constellations	1.3 W
Maximum	2.5 W

### Connectors

Antenna	2 x TNC
ETH	ODU 4 pins
COM1/GPIO	ODU 7 pins
PWR/USB/COM2/COM3	ODU 7 pins

### Antenna LNA power output on TNC

Output voltage	5 VDC
Maximum current	150 mA

### Environmental

Operating temperature	-30° C to +65° C -22° F to +149° F
Storage temperature	-40° C to +75° C -40° F to +167° F

Humidity	MIL-STD-810G, Method 507.5, Procedure I
Dust	MIL-STD-810G, Method 510.5, Procedure I
Shock	MIL-STD-810G, Method 516.6, Procedure I/II
Vibration	MIL-STD-810G, Method 514.6, Procedure I

### Certification

IP 68, RoHS, WEEE, CE  
FCC Class A Part 15  
IEC 62368-1



<sup>1</sup> Open sky conditions

<sup>2</sup> RMS level

<sup>3</sup> Baseline < 40 Km

<sup>4</sup> 99.9%

<sup>5</sup> Including software compensation of sawtooth effect

<sup>6</sup> No information available (no almanac, no approximate position)

<sup>7</sup> Ephemeris and approximate position known



Ihr Partner für Vermessung und Vermarktung  
**JOSEF ATTENBERGER GMBH**

JOSEF ATTENBERGER GMBH, Wasserburger Str. 7, D-84427 Sankt Wolfgang  
www.attenberger.de, info@attenberger.de, Freecall Telefon 0800-2883623  
Fax: +49 (0) 8085-930550 [www.facebook.com/attenberger.gmbh/](https://www.facebook.com/attenberger.gmbh/)  
[www.youtube.de/attenberger](https://www.youtube.de/attenberger) [www.instagram.com/attenberger\\_vermessung](https://www.instagram.com/attenberger_vermessung)  
<https://de.linkedin.com/company/josef-attenberger-gmbh>