




REACH RX

Multi-band network RTK rover



Key features

- Tracks GPS/QZSS1C/A, L2C, GLONASS L1OF, L2OF, BeiDou B1I, B2I, Galileo E1-B/C, E5b
- Gets a fix in 5 seconds
- Centimeter precision
- Easy to set up: just add NTRIP
- Comes with the Emlid Flow app
- Pocket-sized and lightweight
- 16 hours on 1 charge
- IP68



Ihr Partner für Vermessung und Vermarkung

JOSEF ATTENBERGER GMBH

REACH RX

Technical specifications

POSITIONING

Precision	RTK	H: 7 mm+1 ppm V: 14 mm+1 ppm
Convergence time		~5 s typically
Signal tracked		GPS/QZSS L1C/A, L2C, GLONASS L1OF, L2OF, BeiDou B1I, B2I, Galileo E1-B/C, E5b
Number of channels		184
Update rates		5 Hz

CONNECTIVITY

Communication interface		Bluetooth 4.2
Ports		USB Type-C
Input data format		RTCM3
Input data protocol		NTRIP
Position output		NMEA

MECHANICAL

Dimensions		172x51x51 mm (6.77x2.00x2.00 in)
Mount		5/8"-11 UNC
Weight		250g (8.81 oz)
Ingress protection		IP68 (maximum depth of 1.5 meters up to 30 minutes)
Operating t°		-20 to + 65 °C

ELECTRICAL

Autonomy		Up to 16 hrs
Battery		Li-Ion 5200mAh, 3.6V, 18.72Wh
Charging		USB Type-C, 5V, 2A
Certification		FCC, CE, IC

More information about Reach RX



Emlid Software and services

Emlid Studio

Easy-to-use free software to simplify your post-processing workflow.



Emlid Flow

Android & iOS survey app for data management.



Emlid NTRIP Caster

Pass corrections between your RTK GNSS receivers over the Internet.

